

## Brass Pipe Fittings



Description	Part No.	NPT
90° Female Elbow	BP9F-A	1/8
	BP9F-B	1/4
	BP9F-C	3/8
	BP9F-D	1/2
	BP9F-D	1/2
45° Female Elbow	BP4F-A	1/8
	BP4F-B	1/4
Female Tee	BPTF-A	1/8
	BPTF-B	1/4
	BPTF-C	3/8
	BPTF-D	1/2
Female Cross	BPXF-A	1/8
	BPXF-B	1/4
	BPXF-C	3/8
	BPXF-D	1/2
Female Coupling	BPCF-A	1/8
	BPCF-B	1/4
	BPCF-C	3/8
	BPCF-D	1/2
	BPCF-E	3/4

Description	Part No.	NPT
Cap	BPC-A	1/8
	BPC-B	1/4
	BPC-C	3/8
	BPC-D	1/2
	BPC-E	3/4
	BPC-F	1
Square Head Plug	BPSP-A	1/8
	BPSP-B	1/4
	BPSP-C	3/8
	BPSP-D	1/2
Hex Head Plug	BPHP-A	1/8
	BPHP-B	1/4
	BPHP-C	3/8
	BPHP-D	1/2



Description	Part No.	M X F
Pipe Bushing	BPB-BA	1/4 x 1/8
	BPB-CB	3/8 x 1/8
	BPB-DA	3/8 x 1/4
	BPB-DB	1/2 x 1/8
	BPB-DC	1/2 x 1/4
	BPB-EA	1/2 x 3/8
	BPB-EB	3/4 x 1/4
	BPB-EC	3/4 x 3/8
	BPB-ED	3/4 x 1/2



Description	Part No.	M X F
Pipe Adaptor	BPA-AA	1/8 x 1/8
	BPA-BA	1/4 x 1/8
	BPA-BB	1/4 x 1/4
	BPA-CB	3/8 x 1/4
	BPA-CC	3/8 x 3/8
	BPA-DC	1/2 x 3/8
	BPA-DD	1/2 x 1/2
	BPA-ED	3/4 x 1/2
BPA-EE	3/4 x 3/4	



**Max. Working Pressure:**

1. Bar stock, Extruded and Forged:

Fittings up to 3/4 NPT, 1200 psi

2. Cast: 125 psi

Temperature Range: -65 ° to 250 °F

Recommended Assembly:

Hand tighten then turn 2 1/2—3 1/2 turns with wrench



## Brass Pipe Fittings



Description	Part No.	NPT (all)
90° Street Elbow Extruded	BPE9S-A	1/8
	BPE9S-B	1/4
	BPE9S-C	3/8
	BPE9S-D	1/2
	BPE9S-E	3/4
45° Street Elbow Extruded	BPE4S-A	1/8
	BPE4S-B	1/4
	BPE4S-C	3/8
	BPE4S-D	1/2
90° Street Elbow Forged	BPF9S-A	1/8
	BPF9S-B	1/4
	BPF9S-C	3/8
	BPF9S-D	1/2
	BPF9S-E	3/4



Hex Nipple	Part No.	PIPE SIZE
	BPHN-A	1/8
	BPHN-B	1/4
	BPNH-C	3/8
	BPHN-D	1/2
	BPHN-BA	1/4 x 1/8
	BPHN-CB	3/8 x 1/4
	BPHN-DC	1/2 x 3/8



Description	Part No.	NPT (all)
Branch Tee	BPBT-A	1/8
	BPBT-B	1/4
	BPBT-C	3/8
	BPBT-D	1/2
Run (Street) Tee	BPRT-A	1/8
	BPRT-B	1/4
	BPRT-C	3/8
	BPRT-D	1/2



Product	Part No.	Description
Teflon Tape	TT-M8	1/2" x 480"

